U.S. Pat. App. Ser. No. 10/520,604
 Attorney Docket No. 10191/3959

Reply to Office Action of August 20, 2008

AMENDMENTS to the CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1-8 (Canceled).

9. (Currently Amended) A method for notifying a driver of a motor vehicle equipped with an adaptive distance and speed controller, comprising:

one of activating or deactivating a takeover prompt which informs the driver that the vehicle is coming critically close to a target object;

wherein the activation or deactivation of the takeover prompt occurs as a function of at least one of: i) a fixed minimum distance between a distance-controlled and speed-controlled vehicle and the target object, ii) a relative speed-dependent minimum distance of the distance-controlled and speed-controlled vehicle in relation to the target object, and iii) a maximum vehicle deceleration producible by the distance and speed controller, and

wherein the takeover prompt is further output when the driver overrides the distance and speed controller by depressing an accelerator.

10. (Previously Presented) The method as recited in claim 9, wherein the takeover prompt is at least one of: a visual display in a field of view of the driver, and an acoustic signal in an interior of the vehicle.

11. (Canceled).

- 12. (Previously Presented) The method as recited in claim 9, wherein activation thresholds and deactivation thresholds of the takeover prompt are not identical.
- 13. (Previously Presented) The method as recited in claim 9, wherein the distance and speed controller emits and receives radar signals, with the aid of which preceding vehicles can be recognized as target objects.

U.S. Pat. App. Ser. No. 10/520,604
 Attorney Docket No. 10191/3959
 Reply to Office Action of August 20, 2008

14. (Currently Amended) A device for the distance and speed control of a motor vehicle, comprising:

an arrangement which outputs a takeover prompt, informing a driver that the vehicle is coming critically close to a target object, the arrangement being configured so that activation and deactivation of the takeover prompt occurs as a function at least one of: i) a fixed minimum distance between the distance- and speed-controlled vehicle and the target object, ii) a relative speed-dependent minimum distance between the distance- and speed-controlled vehicle and the target object, and iii) a maximum vehicle deceleration producible by the distance and speed controller, wherein the takeover prompt is further output when the driver overrides the distance and speed controller by depressing an accelerator.

- 15. (Previously Presented) The device as recited in claim 14, further comprising:
 a display device, the display device displaying the takeover prompt in a field of view of the driver.
- 16. (Currently Amended) The device as recited in claim 14, further comprising:
 an acoustic device, the takeover prompt being [[about]] output as an acoustic signal
 by the acoustic device in an interior of the vehicle.
- 17. (Currently Amended) The device as recited in [[one]] [[of]] claim 14, further comprising: a radar device, the radar device configured to emit and receive radar signals so that a preceding vehicle can be recognized as a target object.
- 18. (Previously Presented) The device as recited in claim 14, further comprising:
 a display device, the display device displaying the takeover prompt in a field of view of the driver; and

an acoustic device, the takeover prompt being about output as an acoustic signal by the acoustic device in an interior of the vehicle.

19. (Previously Presented) The device as recited in one of claim 18, further comprising:
a radar device, the radar device configured to emit and receive radar signals so that a
preceding vehicle can be recognized as a target object.

3

NY01 1603208

U.S. Pat. App. Ser. No. 10/520,604
 Attorney Docket No. 10191/3959
 Reply to Office Action of August 20, 2008

20. (Canceled).

- 21. (Currently Amended) The method as recited in claim [[20]] 14, wherein activation thresholds and deactivation thresholds of the takeover prompt are not identical.
- 22. (Previously Presented) The method as recited in claim 21, wherein the distance and speed controller emits and receives radar signals, with the aid of which preceding vehicles can be recognized as target objects.
- 23. (New) The device as recited in claim 14, further comprising:

at least one of a display device, the display device displaying the takeover prompt in a field of view of the driver, and an acoustic device, the takeover prompt being output as an acoustic signal by the acoustic device in an interior of the vehicle; and

a radar device, the radar device configured to emit and receive radar signals so that a preceding vehicle can be recognized as a target object;

wherein activation thresholds and deactivation thresholds of the takeover prompt are not identical, and

wherein the distance and speed controller emits and receives radar signals, with the aid of which preceding vehicles can be recognized as target objects.

24. (New) The method as recited in claim 9, wherein the takeover prompt is at least one of: a visual display in a field of view of the driver, and an acoustic signal in an interior of the vehicle, wherein activation thresholds and deactivation thresholds of the takeover prompt are not identical, and wherein the distance and speed controller emits and receives radar signals, with the aid of which preceding vehicles can be recognized as target objects.